

型号	KY-30KW-130KWH		KY-40KW-172KWH		KY-50KW-215KWH		KY-60KW-215KWH	
光伏输入参数								
最大输入电压	1000V							
MPPT工作电压范围	180-900/630V							
最大输入功率	36W		48W		60W		72W	
额定输入电压	630V							
最大输入电流	36A/36A/36A				36A/36A/36A/36A			
最大短路电流	42A/42A/42A				42A/42A/42A/42A			
MPPT路数/组串数	2/2/2				2/2/2/2			
端子连接方式	快插							
并网端口参数(AC)								
额定功率	30000W		40000W		50000W		60000W	
最大视在功率	30000VA		40000VA		50000VA		60000VA	
额定电压	400V,3L/N/PE							
额定频率	50Hz/60Hz							
最大电流	45A		60A		75A		87A	
功率因数范围	0.8 ind...0.8 cap							
电流总谐波失真(@额定功率)	<3%							
UPS端口参数(AC)								
额定电压	400V,3L/N/PE							
额定频率	50Hz/60Hz							
额定输出电流	45A		60A		75A		87A	
额定输出功率	30000W		40000W		50000W		60000W	
最大视在输出功率	30000VA		40000VA		50000VA		60000VA	
峰值功率	36000/10sW		48000/10sW		60000/10sW		72000/10sW	
最大单相视在输出功率(VA)	10000VA		13000VA		17000VA		20000VA	
并网网切换时间	<10ms							
电池参数								
工作电压范围	432-518V		576-691V		720-864V		720-864V	
充放电功率	30000W		40000W		50000W		60000W	
最大充电/放电电流	100A/100A							
额定容量	130kWh		172kWh		215kWh		215kWh	
可用容量	120kWh		160kWh		200kWh		200kWh	
基本参数								
尺寸 (W*D*H)	1200*1200*2200mm							
防护等级	IP54							