

DATASHEET

6-10KW Three-Phase Hybrid Inverter				
Model		EST-6K0H	EST-8K0H	EST-10K0H
Efficiency	Max.Efficiency	>98.2%		
PV Input and Output	Max. PV input power(W)	7800	10400	13000
	Max. PV input voltage(V)	1000		
	MPP Operation Voltage Range(V)	180-900		
	No. of MPPTs	2		
	Max. number of PV strings per MPPT	1/1	1/1	1/1
	Max. PV input current(A)	12.5/12.5	12.5/12.5	
	Short-circuit current of PV input(A)	13.5/13.5	13.5/13.5	
	Start up voltage(V)	180		
Battery Input	Max Input/Output Voltage(V)	550		
	Operating Voltage Range(V)	180-550		
	Max Charge/Discharge Current(A)	25/30		
	Max Input/Output Power(W)	6000/6000	8000/8000	10000/10000
	Battery Type	Li-ion/Lead-acid		
AC Input and Output	Rated Power(W)	6000	8000	10000
	Max. Apparent AC Power(VA)	6000	8000	10000
	Nominal AC Voltage(Vac)	380,3L/N/PE		
	AC Power Frequency(Hz)	50/60		
	Max. AC Output Current(A)	10	12	15
	Rated Current Output(A)	10	12	15
	Power Factor Range	~1 (Adjustable from 0.8 leading to 0.8 lagging)		
	OutputTHDi(@Nominal Output)	<3%		
Off-Grid AC Output(Back-up AC Output)	Rated Output Power(W)	6000	8000	10000
	Max. Apparent AC Output Power(VA)	6000	8000	10000
	Nominal AC Output Voltage(Vac)	380,3L/N/PE		
	AC Power Frequency(Hz)	50/60		
	Max. AC Output Current(A)	10	12	15
General Data	Operating Temperature Range	-25°C ... +60°C(>45°C derating)		
	Operating Altitude(m)	<4000		
	Noise(dB)	<40		
	Topology	Transformerless		
	Cooling Method	Natural convection		
	Ingress Protection Rating	IP65		
	Relative Humidity	0-100%, no condensation		
	DC Connection Type	MC/Amphenol/Phoenix		
	AC Connection Type	Plug-in Connector		
	Display	LCD		
	Communication With Portal	RS485 (WiFi/GPRS Optional)		
	Communication With BMS	CAN		
	Communication With Meter	RS485		
	Mounting Method	Wall-mounting bracket		
	Dimensions (W*H*D)(mm)	505*570*220		
	Weight(Kg)	23	23	24
Certification	Safety	IEC62109-1/-2		
	EMC	EN61000-6-1/-2/-3,IEC61000		
	On-Grid standard	AS4777.2,NRS097-2-1:2017		
Country of origin	Made in China			

DATASHEET

12-20KW Three-Phase Hybrid Inverter					
Model		EST-12KH	EST-15KH	EST-17KH	EST-20KH
Efficiency	Max.Efficiency	>98.2%			
PV Input	Max. PV input power(W)	15600	19500	22100	26000
	Max. PV input voltage(V)	1000			
	MPP Operation Voltage Range(V)	180-900			
	No. of MPPTs	2		4	
	Max. number of PV strings per MPPT	1/1	2/1	2/2	
	Max. PV input current(A)	12.5/12.5	12.5/23	23/23	
	Short-circuit current of PV input(A)	13.5/13.5	13.5/25	25/25	
	Start up voltage(V)	180			
	Battery	Max Input/Output Voltage(V)	700		
Operating Voltage Range(V)		180-700			
Max Charge/Discharge Current(A)		50/50			
Max Input/Output Power(W)		12000/12000	15000/15000	17000/17000	20000/20000
Battery Type		Li-ion/Lead-acid			
AC Input and Output	Rated Power(W)	12000	15000	17000	20000
	Max. Apparent AC Power(VA)	12000	15000	17000	20000
	Nominal AC Voltage(Vac)	380,3L/N/PE			
	AC Power Frequency(Hz)	50/60			
	Max. AC Output Current(A)	18	22	25	31
	Rated Current Output(A)	18	22	25	31
	Power Factor Range	~1 (Adjustable from 0.8 leading to 0.8 lagging)			
	OutputTHDi(@Nominal Output)	<3%			
Off-Grid AC Output(Back-up AC Output)	Rated Output Power(W)	12000	15000	17000	20000
	Max. Apparent AC Output Power(VA)	12000	15000	17000	20000
	Nominal AC Output Voltage(Vac)	380,3L/N/PE			
	AC Power Frequency(Hz)	50/60			
	Max. AC Output Current(A)	18	22	25	31
General Data	Operating Temperature Range	-25°C ...+60°C(>45°C derating)			
	Operating Altitude(m)	<4000			
	Noise(dB)	<45			
	Topology	Transformerless			
	Cooling Method	Intelligent Fan			
	Ingress Protection Rating	IP65			
	Relative Humidity	0-100%, no condensation			
	DC Connection Type	MC/Amphenol/Phoenix			
	AC Connection Type	Plug-in Connector			
	Display	LCD			
	Communication With Portal	RS485 (WiFi/GPRS Optional)			
	Communication With BMS	CAN			
	Communication With Meter	RS485			
	Mounting Method	Wall-mounting bracket			
	Dimensions (W*H*D)(mm)	505*630*220			
	Weight(Kg)	26	27	27	28
Certification	Safety	IEC62109-1/-2			
	EMC	EN61000-6-1/-2/-3,IEC61000			
	On-Grid standard	AS4777.2,NRS097-2-1:2017			
Country of origin	Made in China				